



## Robex Road Line Paint

Cost effective hard wearing solutions for marking lines



**In Person:** Should you have any queries regarding product application, one of our trained sales engineers is always on hand to sort out any problems you may have.



**On line:** All of our technical data sheets and health & safety data sheets are available to download on line.



**On site:** If you would like Robex to apply your product for you call on the number below, we manufacture, we supply and we apply.



## Robex Road Line Paint

- Easy to apply –single pack applied by brush
- Good chemical resistance
- Hard wearing
- Quick curing
- Suitable for internal and external use

Road Line Paint is a hard wearing single pack line marking resin for use on almost any surface including wood, concrete, asphalt and tarmac.

Easily applied by brush or roller, Road Line Paint is unaffected by sunlight.

○ White   ● Yellow   Other colours available on request

## Robex Road Line Paint

- **Preparation**

The surface to be painted must be dry and free from oil, dust, road salts and other contaminants before application.

Preparation by captive blast is recommended for very smooth block pavers

**Coating Galvanized Iron and Zinc/Aluminium and its Alloys:** Special preparation/priming is required for these surfaces depending on the age and condition. Please refer to our technical department before applying any Robex coating to this type of surface.

- **Application**

Apply with a solvent friendly, medium roller, brush or by airless spray.

Recommended tip sizes 17-19

Tip angles as an indication

20° 50 mm line

30° 75 mm line

40° 100 mm lines

Mix thoroughly prior to use and do not apply when the air or surface temperature is less than 5°C.

Application should also be avoided if rain is imminent or there is mist, fog or high humidity (minimum 3° above dew point and less than 80%)

- **Drying Time**

Touch @ 20°C: 12 minutes at 700 microns (will vary with temperature)

- **Coverage**

Approximately 200 metres of a 50 mm line per 6kgs depending on the porosity of the surface. One coat normally sufficient.

- **Cleaning**

To clean brushes, equipment, contaminants, etc., we recommend the use of Robex Cleaning Solvent RX117.

- **Shelf Life**

12 months under good storage conditions

Can be stored for a period of 12 months in its original packaging if not opened. Temperature range 50°C to 35°C.

- **Health & Safety**

Please refer to the relevant Health and Safety Data Sheet.

26.04.16

No liability is accepted for any injury, loss or damage arising directly or indirectly from the use of the Company's products or from the use of information given in our data sheets, since the customer's use of the product is necessarily out of our control. The information given is intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that the products are suitable for their intended use.