

Robex Watershield Plus

A special blend of aliphatic solvents reinforced by polyoxoaluminium stearate



In Person: Should you have any queries regarding product application, one of our trained sales engineers is always on hand to sort out any problems you may have.



On line: All of our technical data sheets and health & safety data sheets are available to download on line.



On site: If you would like Robex to apply your product for you call on the number below, we manufacture, we supply and we apply.



Robex Watershield Plus

- Easily applied by brush or spray
- Reduces the risk of damage caused to masonry by the freeze/thaw cycle
- Allows surfaces to breathe
- Helps prevent growth of mildew, moss and lichen

Robex Watershield Plus is designed to prevent penetrating damp and can be applied by brush or spray onto brick, stone, concrete, masonry and other porous surfaces. Once cured, Watershield Plus will produce an invisible hydrophobic barrier and the treated surfaces will repel water, however, the vapour permeability will be unaffected allowing the walls to breathe. Watershield Plus meets the requirements of BS6477:1992 specification for Water Repellents for Masonry Surfaces.

Robex Watershield Plus

- **Preparation**

Remove any moss, lichen or algae growth and allow to dry thoroughly.

Ensure all mortar and pointing is in good condition and cracks and fissures are made good.

Cover windows to avoid splashes on glass UPVC or paintwork.

Watershield Plus is not suitable for use on new work.

All surfaces should be clean and free from dust and grease. Any moss, lichen or algae should be removed using a fungicidal wash. All cracks and holes should be made good.

- **Application & Cure Time**

Watershield Plus is supplied ready to use.

Apply by brush or low-pressure spray working upwards from the bottom.

A minimum of two coats is recommended, however, on extremely porous surfaces or exposed sites three coats may be necessary.

Allow a minimum of 4 hours between coats; ensuring the first coat has soaked in thoroughly.

After treatment the wall will exhibit a pronounced beading effect after rain. The beading effect diminishes slow over 6 months but the water repellency of the Watershield Plus is not impaired.

- **Coverage**

Approximately 12-15m² per 5 litre unit depending on surface profile and porosity.

- **Precautions**

Do not apply to visibly wet walls, as no penetrate of Watershield Plus will be achieved.

Watershield Plus is colourless but by the nature of drying out the substrate can highlight differences in its make up. If in doubt always treat a small area first.

Remove all splashes on windows, etc., as soon as possible. If necessary soften up any splashes using a propriety windscreen car wash and apply vigorous rubbing with a cloth.

- **Storage Life**

12 months in original sealed containers.

Replace lid securely after use. Any remaining product should be used up as soon as possible after use. Exposure to the atmosphere reduces shelf-life considerably.

- **Health & Safety**

R65: Harmful may cause lung damage if swallowed.

Keep away from all potential sources of ignition. Ensure adequate ventilation and wear suitable clothing. Wash splashes from skin and eyes immediately.

Please refer to the relevant health and safety data sheet.